


Product Data Sheet

Edition 01, 2008

Version No. 001

Fastener SB-6.3 x L

Fastener SB-6.3 X L



Overview	Carbon steel screw with Durocoat F coating	
Material	Hardened carbon steel	
Basic size	Thread diameter	6.3 mm
	Drilling point Dia.	3.4 mm
	Head & Drive type	Flat head ,drive T30
Corrosion resistance	15 cycles Kesternich test	
Approval	FM approval for Chinese Application	
Specification	6.3x 32 mm	500Pcs
	6.3x 50 mm	500Pcs
	6.3x 75 mm	500Pcs
	6.3x 100 mm	500Pcs
	6.3x 120 mm	500Pcs
	6.3x 140 mm	500Pcs
	6.3x 160 mm	250Pcs
	6.3x 180 mm	250Pcs
	6.3x 200 mm	250Pcs
	6.3x 230 mm	250Pcs
	6.3x 250 mm	250Pcs
Application	On qualified substrate, including concrete, steel deck, wood, etc.;; Normal environment, humidity below 70% and no chemical condition.	

All data in our product information are based on our current knowledge and experience. They do not release users from careful testing of the application and strict observation of the relevant processing regulations because of the wide range of possible influences during the application and use of our products. Legally valid assurances of specific characteristics or suitability for special purposes of application other than those provided in our documentation for the specific product cannot be inferred from our information. The recipient or processor of our products at their own responsibility must follow any protective rights or existing laws and provisions. Moreover our general terms and conditions of sale and warranty are valid.



Sarnafil Waterproofing Systems (Shanghai) Ltd.
No. 4555 Hua Ning Rd., Xinzhuang Industry Park
Shanghai 201108, China

Phone +86 21 3407 3788
Fax +86 21 3407 3800
www.sarnafil.com.cn

Sarnafil®